

**TECHNICAL  
DATA  
SHEET**

# GF 830 AUTOMARK™ CAST WITH DRIFT® TECHNOLOGY

2.0 MIL GLOSS WHITE WRAP VINYL  
SLIDABLE REPOSITIONABLE AIR-EGRESS ADHESIVE

GF 830 AutoMark™ Cast with DRIFT® Technology is a 2.0 mil, high-gloss white cast film with a slidable and repositionable grey adhesive system. The DRIFT Technology and air egress feature provides installers the benefit of a slidable and bubble-free installation. The repositionable grey long-term removable adhesive delivers excellent opacity for color blocking possible substrate bleed through. GF 830 is specifically engineered for automotive OEM paint, complex curves, rivets, and perfect for vehicle and fleet applications. Compatible with a variety of solvent, eco-solvent, latex and UV curable inks

PRODUCT NAME	830
<b>FILM</b>	
Film Type	Cast White Vinyl
Film Thickness (mils/μm)	2.0 / 50 (+/- 10%)
Film Weight (gsm)	78
Gloss (60°)	≥90
Opacity (%)	99
Elongation (%)	MD ≥ 200
Dimensional Stability (FTM 14)	MD ≤ 0.35 mm
<b>ADHESIVE</b>	
Adhesive Type	Solvent Acrylic
Adhesive Thickness (mils/μm)	1.2-1.4 / 30-36
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	2.5 / 11
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	3.0 / 13
<b>LINER</b>	
Liner Weight (#/gsm)	106 / 160 (+/- 10%)
Liner Type	White 2-sided PE-Coated Kraft, Slideable Air-Egress
Liner Thickness (mils/μm)	8.0 / 200
Release Force @ 300" / min (g/2")	80-120
<b>PERFORMANCE GUIDANCE</b>	
Application Temperature	≥ +50 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	2 years
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	8 years
Long-Term Removability	* 4 year Clean Removability

\* Removal may require heat. Up to 20% adhesive transfer may occur in certain situations.

# TECHNICAL DATA SHEET

**GF 830 - 2.0 MIL GLOSS WHITE WRAP VINYL  
GREY SLIDABLE REPOSITIONABLE AIR-EGRESS ADHESIVE**

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p><b>APPLICATION</b></p> <ul style="list-style-type: none"> <li><input type="radio"/> WET APPLY</li> <li><input checked="" type="radio"/> DRY APPLY</li> <li><input type="radio"/> LAMINATING</li> <li><input type="radio"/> MOUNTING</li> <li><input checked="" type="radio"/> DIE CUTTABLE</li> <li><input type="radio"/> HOT STAMP</li> <li><input checked="" type="radio"/> FLATBED CUTTABLE</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> POP/RETAIL</li> <li><input checked="" type="radio"/> WALL (PERMANENT APPLICATION)</li> <li><input checked="" type="radio"/> WRAP</li> <li><input checked="" type="radio"/> WINDOW</li> <li><input type="radio"/> FLOOR</li> <li><input checked="" type="radio"/> FLEET</li> <li><input checked="" type="radio"/> GENERAL SIGNAGE</li> <li><input checked="" type="radio"/> INDOOR</li> <li><input checked="" type="radio"/> OUTDOOR</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> SOLVENT</li> <li><input checked="" type="radio"/> ECO-SOLVENT</li> <li><input checked="" type="radio"/> LATEX</li> <li><input checked="" type="radio"/> UV CURABLE</li> <li><input checked="" type="radio"/> SCREEN</li> <li><input checked="" type="radio"/> OFFSET (UV CURABLE)</li> <li><input type="radio"/> OFFSET (CONVENTIONAL)</li> </ul>
<p><b>SUBSTRATES</b></p> <ul style="list-style-type: none"> <li><input checked="" type="radio"/> OEM PAINTED METAL</li> <li><input checked="" type="radio"/> PAINTED ALUMINUM</li> <li><input checked="" type="radio"/> STAINLESS STEEL (MIRRORED)</li> </ul>	<p><b>MATCHING LAMINATES</b></p> <ul style="list-style-type: none"> <li><input checked="" type="radio"/> GF 813 - 1.3 MIL GLOSS CAST CLEAR UV</li> <li><input checked="" type="radio"/> GF 831 - 2.0 MIL GLOSS CAST CLEAR UV</li> <li><input checked="" type="radio"/> GF 840 - 2.0 MIL MATTE CAST CLEAR UV</li> <li><input checked="" type="radio"/> GF 844 - 2.0 MIL ULTI-MATTE CAST CLEAR UV</li> </ul>	<p><b>ADDITIONAL LAMINATES</b></p> <ul style="list-style-type: none"> <li><input checked="" type="radio"/> GF 242 - 2.0 MIL GLOSS CAST OPTICALLY CLEAR UV</li> <li><input checked="" type="radio"/> GF 108 - 1.0 MIL SATIN ANTI-GRAFFITI LAMINATE (GF 108 IS FLAT APPLICATION ONLY)</li> </ul>

## FAQS

Can I use AutoMark™ Cast w/Drift® Technology for full vehicle wraps?	Yes. This is a wrapping film perfect for complex curves, deep channels, rivets, and false recesses.
What does “slidable” mean?	The slidable adhesive allows you to literally slide the film on the OEM painted surface and easily reposition as needed. Once pressure is applied to the film surface, the adhesive is then activated.
Can you use liquid laminates?	Contact your General Formulations Regional Sales Manager. <a href="#">Contact Page.</a>
Can GF 830 be used on fiberglass boats?	Contact your General Formulations Regional Sales Manager. <a href="#">Contact Page.</a>
Can GF 830 be used on ceramic coatings?	Ceramic coatings can cause poor adhesive bond and must be removed.
Can GF 830 be used for cut lettering?	Yes. Must be tested for your specific use.